



MARS X

HDMI Wireless Video Transmitter



300ft Transmission
Range (LOS)



Video & Audio
Synchronization



<0.07s
Ultra-Low Latency



OLED
Display Screen



APP
Monitoring



Portable and Compact



APP Firmware
Upgrade



Smart
Channel Scan



Built-In Battery



Multiple Power
Supply Options

Parameter

Interface	HDMI Input (Type A Female), USB Type-C Power Interface, Micro USB
Power Consumption	<4W
Work Temperature	-10~+60°C
Display Size	0.69"
Maximum Device Connections Allowed	3 Devices
Net Weight	112g
Dimension	L*W*H (Antennas Collapsed) :90*50*18mm; L*W*H (Antennas Opened) :155*50*18mm
Input Video Format	HDMI:480p60, 576p50, 720p50/59.94/60, 1080p23.98/24/25/29.9/30/50/59.94/60
Frequency	5GHz
Modulation Mode	OFDM
Transmission Power	Maximum 20dBm
Bandwidth	40MHz
Built-In Battery Life for Each Charge	>1 Hour
Battery Charging Time	2.5 Hours
Low-Battery Warning Voltage	3.65V
USB Type-C Power Supply Range	5~12V
Default WiFi Password (Check and Change the Password on the APP)	12345678

Packing List



Transmitter



Type-C to Type-A USB Cable



User Manual



Cold Shoe to 1/4"-20 Mount



Storage Bag

* Please subject to actual shipment as the standard if any difference in accessories.



www.hollyland-tech.com

