HOLLYLAND

For a better view!


SHENZHEN HOLLYLAND TECHNOLOGY CO.,LTD

8F, Building 5#D, Skyworth Innovation Valley
Tangtou Road,Shiyan Street, Baoan District
Shenzhen, China
86-755-8600-0682

SYSCOM 3000

Ultra-Long Wireless Video Transmission With Strong Signal

1.(RSSI)Received Signal Strength Indicator
2.Link Indicator
3.Video Indicator
4.7-Seg LED Frequency Channel Indicator
5.Selection Button
6.Confirm Button







RECEIVER

Features

- Transmission Range: 3000ft
- Channel Selection: 0-4 (USA) / 0-9 (Outside of USA)
- USB Firmware Upgrade
- No Compression, No Latency
- Point to Point & Broadcast Mode
- 3G-SDI In/Loop Out/, HDMI In/Out
- 5GHz ISM Frequency Band
- 3G-SDI Level B

Highlights



Compatible with Cosmo Transmitters



Long Range Up to 3000ft



Built-in Antennas

Copyright © Hollyland Technology Co.,Ltd

Packing List



Allen key * 1



User Manual*1



D-tap to Lemo Cables*1





Receiver*1



USB Cable *1



Tripod mount adapter*1

Application



Monitor



Receiver



3000ft



Transmitter



Camera

	Transmitter	Receiver
Interface	SDI input(BNC female); SDI loop out(BNC female) HDMI input(Type A female); 2 Antenna port(RP-SMA male) DC input(4pin LEMO female);Mini USB port; 3.5mm Analog invoice input port	SDI1 output(BNC female); SDI2 output(BNC female) HDMI output(Type A female); DC input(4pin LEMO female); Mini USB port
Supply Voltage Range	7-36V DC	7-36V DC
Power Consumption	<7W	<7.5W
Weight	536g	2500g
Size	(L xWxH):145.5x89.7x25mm, not include antennas and battery plate	(LxWxH):305x 305 x 110mm
Input Video Format	HDMI:480p60,576p50,720p50/59.94/60, 1080i50/59.94/60, 1080p23.98/24/25/29.9/30/50/59.94/60; HDMI Type A; SDI:3G, HD, and SD-SDI (auto-selected); SMPTE-259/274/292/296/372/424/425;1x BNC; 1x BNC Loopout;	/
Output Video Format	/	HDMI:480p60,576p50,720p50/59.94/60, 1080i50/59.94/60, 1080p23.98/24/25/29.9/30/50/59.94/60; HDMI Type A; SDI:3G, HD, and SD-SDI (auto-selected); SMPTE-259/274/292/296/372/424/425; 2x BNC output;
Input Audio	SDI/HDMI embedded 2 channel 24 bit/48KHZ	/
Output Audio	/	SDI/HDMI embedded 2 channel 24 bit/48KHZ
Signal Indicator	link: Green Video: Yellow	link: Green Video: Yellow RSSI-Blue(5 LEDs)
Frequency Band	5.1-5.9GHz,configurable with China, North America, Europe,et	5.1-5.9GHz,configurable with China, North America, Europe,et
Modulation Mode	OFDM-16QAM	OFDM-16QAM
Transmission Power	Maximum 18dBm	/
Receiver Sensitivity	/	-75dBm
Occupied Bandwidth	40MHz	40MHz