
HOLLYLAND
For a better view!

SHENZHEN HOLLYLAND TECHNOLOGY CO.,LTD
8F, Building 5#D, Skyworth Innovation Valley
Tangtou Road,Shiyan Street, Baoan District
Shenzhen, China
86-755-8600-0682

SYSCOM 1500VT

1500FT Wireless HDMI/SDI Transmission System and Intercom



Features

- Audio & Video Working Distance: 1500ft, up to 2000ft
- Wireless Intercom & Wireless Tally
- No Compression, NO Latency
- HDMI, SDI input/output, SDI loop output
- Point to Point & Broadcast Mode
- Fixed Antennas
- Time code & Trigger
- True Full HD 1080P60
- Wide Voltage: 7V-36V DC
- Channel Selection:0-4/Outside USA:0-9
- USB Firmware Upgrade
- Full Duplex Intercom
- Double side V-Lock battery plate

Highlights

Supply Voltage: 7-36VDC

REC TC 0:00:00
Trigger & Timecode

Full Duplex Wireless Communication

USB firmware upgrade

Support Tally

Double Side Battery Plate

Copyright © Hollyland Technology Co.,Ltd

Packing List



Hard Case*1


5 GHz Antennas*15


Magic Arm*1


Allen key*1


DC Conversion Cables*2


Transmitter*1


Receiver*1



User Manual*1


Headsets*2

	Transmitter	Receiver
Interface	SDI input/loop out（BNC female）; HDMI input（Type A female）; 4xSMA antenna port; 1x Mini USB; DC input; 3.5mm HP/MIC socket; 3.5mm TALLY socket;	2xSDI output（BNC female）; HDMI output（Type A female）; 7xSMA antenna port; 1x Mini USB; DC input; 3.5mm HP/MIC socket; 3.5mm TALLY socket;
Voltage Range	7–36V DC	7–36V DC
Consumption	< 9W	< 9W
Weight	950g	1050g
Size	(LxWxH):180*115*30mm, not include antennas and battery plate	(LxWxH):180*120*30mm, not include antennas and battery plate
Input Audio	SDI/HDMI embedded 2channal 24 bite/48KHz	/
Output Audio Format	/	SDI/HDMI embedded 2channal 24 bite/48KHz
Input Video Forma	HDMI: 1080p23.98/24/25/29.9/30/50/59.94/60, 1080i 50/59.94/60, 720p 50/59.94/60, 625i , 525i; SDI: 3G, HD, and SD–SDI ; SMPTE–259/274/292/296/372/424/425	/
Output Video Format	/	HDMI: 1080p23.98/24/25/29.9/30/50/59.94/60, 1080i 50/59.94/60, 720p 50/59.94/60, 625i , 525i; SDI: 3G, HD, and SD–SDI ; SMPTE–259/274/292/296/372/424/425
Frequency Band	5.1–5.9GHz, configurable with China, North American, Europe, etc; 2.4–2.485GHz ISM frequency band	
Modulation mode & Occupied Bandwidth	OFDM/40MHz（Video） GFSK/1MHz（Full duplex wireless intercom）	/
Transmission Power	Max.:19dBm	(5Leds)
Signal Indicator	Link: Green; Video: Yellow; 2.4G connecting: Red	Link: Green; Video: Yellow; 2.4G connecting: Red RSSI: Blue
Receiver Sensitivity	/	–75dBm